

Christie Captiva Series

Conference rooms Museums
Education Retail
Huddle spaces



Maximize your space, captivate your audience

Captivate audiences, inspire creativity and nurture collaboration with the Christie® Captiva Series of 1DLP® lampless ultra short throw projectors.

Maximize your space without sacrificing visual impact with one of the shortest throw distances on the market. Empower your content by creating canvases up to 140" diagonal in landscape or portrait mode, easily add interactivity capabilities and run multiple applications simultaneously.

With the choice of standard HD or ultra wide aspect ratios, the Christie Captiva Series allows you to create and share unique user experiences whether it's in the classroom, conference room or retail environment.

Based on laser phosphor illumination, the Christie Captiva Series provides 20,000 hours of low cost and reliable operation and offers a suite of easy-to-use features, multiple mounting options and instant on/off, letting you focus on what's important - the content.

CHRISTIE®

		Christie Captiva DHD400S 140-012104-01	Christie Captiva DUW350S 140-011103-01
Image	brightness (lumens)	• Center - 3500 • ANSI - 3100 • ISO - 3500	• Center - 3000 • ANSI - 2700 • ISO - 3000
	contrast	• 1800:1 Full on/off	
Display technology	type	• 1-chip 0.65" DMD	• 1-chip 0.65" DMD
	native resolution	• 1920 x 1080 (2,073,600 pixels) 16:9	• 1920 x 720 (1,382,400 pixels) 16:6
	image size (diagonal)	• 80-100"	• 100-140"
Illumination	type	• Solid state (Laser phosphor)	
	typical lifetime	• 20,000 hrs	
Signal inputs	standard	• HDMI x 2 • VGA x 1 + monitor out or VGA x 2 • VGA audio in (3.5mm phone jack) • Composite video x 1 (RCA) + audio (RCA x 2) • Microphone input • USB A (for use with optional Wireless Dongle)	
	max input pixel rate	• 1600 x 1200 @ 60Hz (162 MHz) • 1920 x 1200 @ 60Hz reduced blanking (154 MHz)	
	3D	• Frame packed/side-by-side/top and bottom 3D (HDMI 1.4a) • Frame sequential DLP link 3D (VGA/HDMI) • Frame sequential/field sequential HQFS 3D (Composite/S-Video)	
	pixel clock	• 162 MHz	
Signal outputs	• VGA monitor out (or second VGA in) • 10W speaker • Audio output (3.5mm phone jack)		
Control and networking	• RS-232 in • Ethernet (100BaseT) RJ45 • Built-in keypad • Compatible with Crestron RoomView, AMX, PJ Link		
Accessories	standard	• IR remote • AC Line cord for projector Head • VGA cable • Camera for interactivity accessories • User manual	
	optional	• Wall mount • IR pens • Captiva Touch (laser IR curtain)	
Lens	adjustment	• Focus adjustment	
	lens	• 0.25:1 ultra short throw lens	
	offsets	• Fixed offset based on image size	
Power requirements	operating voltage	• 100-240 VAC @ 50/60Hz	
	power consumption	• 335W max • 225W eco mode	
	operating current	• 3.5A max	
	dissipation	• 1143 BTU/hr max • 768 BTU/hr eco mode	
Audible noise	• Standard mode: 36dB (A) • Eco mode: 32dB(A)		
Physical	size	• (LxWxH) 12.20 x 15.08 x 4.06" (310 x 383 x 103mm) w/o feet	
	shipping size	• 12.1lbs (5.5 kg)	
	weight	• (LxWxH) 19 x 16.5 x 12.9" (483 x 420 x 328 mm)	
	shipping weight	• 19.4lbs (8.8kg)	
Operating environment	temperature	• Temp: 40-104° F (5-40° C)	
	humidity	• Humidity: 5-90% non-condensing	
Regulatory	• This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • UL/CSA/IEC 60950-1 • FCC Class A • CE • CCC • KC • PSE • VCCI • CU • BIS • RCM and SABS		
Warranty	• Three years on the projector • Three years or 15,000 hours on the illumination system ¹ • Contact an authorized Christie representative for full details of our limited warranty		

¹ Reference the Christie Standard Limited Warranty document for details

Christie support and services

All Christie products are backed by industry-leading warranties, renowned service and support. We ensure our customers are well supported with training, service and technical knowledge through our extensive distribution and support network.

United Kingdom
Branch & EMEA
Head Office
ViewPoint
200 Ashville Way
Wokingham
Berkshire, U.K.
RG41 2PL
PH: +44 (0) 118 977 8000

Middle East
Light Industrial Unit (LIU-17)
Nad Al Shibba
Sheikh Mohammed Bin Zayed Road
Dubai Silicon Oasis
PO Box: 293762
Dubai - U.A.E
PH: +971 (0) 4 503 6800

Africa
Unit C3
Northlands Deco Park
New Market Road
Northriding
Randburg
2164
Johannesburg
Gauteng
South Africa
PH: +27 71 335 8667

Other EMEA offices

Germany
Branch Office
PH: +49 2161 566 200

France
Branch Office
PH: +33 (0) 1 41 21 44 04

Eastern Europe
Representative Office
PH: +36 (0)1 47 48 138

Spain
Branch Office
PH: +34 91 633 9990

Italy
Independent Sales Consultant Office
PH: +39 (0) 2 9902 1161

Russia
Independent Sales Consultant Office
PH: +7 (495) 930-8961



For the most current specification information, please visit www.christieemea.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4102 Sep 15

CHRISTIE®